MATERIAL SAFETY DATA SHEET May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910 1200. Standard must be consulted for specific requirements.

U.S. DEPARTMENT OF LABOR Occupational Safety and Health Administration (Non-Mandatory Form)

(Non Mandatory Form) Form Approved OMB No. 1218-0072 H.M.I.S RATING
HEALTH: 1
FLAMMABILITY: 0
REACTIVITY: 0
PERSONAL PRO-

for specific requirements.

OMB No. 1218-0072

EHEET MEMBRANE IN ROLL FORM

IDENTITY (as used on label and fast)

NOTE: Blank spaces are not permitted, if any item is not applicable, or no information is available, the space must be marked to indicate that.

Elasto-Seal 2000

SECTION I

Manufacturer's Name

Emergency Telephone Number

Manufacturer's Name	Emergency Telephone Number 610-933-8888 Telephone Number for Information 610-933-8888						
MONSEY BAKOR ADDRESS (Number, Street, City, State and Zip Code)							
P.O. BOX 366							
COLD STREAM ROAD	Date Prepared Supersedes Sheet #938						
	5/14/98 1/8/98						
KIMBERTON, PA 194	Signature of Preparer (optional)						
SECTION II HAZARDOUS	INGREDIENTS/IDEN	ITITY INFORMATION		<del></del>			
	- III - III - A			Other Limits	Be do sale so the		
Hazardous Components (Specify	Chemical Identity;Common CAS#	Name(s)) OSHA PEL A	GIH TLV	Recommended	%(optional)		
	Cr 10II						
PETROLEUM ASPHALT	8052-42-4	5r	ng/m³		70 - 60		
<del></del>	<del></del> ,	<del></del>					
<del></del>							
					<del></del>		
SECTION III PHYSICAL/C	HEMICAL CHARACT	TERISTIÇS					
Boiling Pt.	N/A	Weight per gallon		<u>75-9.1</u>			
Vapor Pressure(mm Hg)	N/A	Melting Point		N/A_			
Vapor Density(Air=1)	N/A	Evaporation Rate (Butyl Acel	ate=1)	N/A			
Solubility in Water	insolubie						
<del></del>	<del> </del>						

EXTINGUISHING MEDIA: Foam, cerbon dioxide, dry chemicals and water

399°F (COC)

SECTION IV FIRE AND EXPLOSION HAZARD DATA

SPECIAL FIRE FIGHTING PROCEDURES: Use water spray or log to keep fire-exposed containers cool. Do not point solid water directly into burning asphalt to avoid spreading. Self-contained breathing apparatus and fire protective clothing should be worn when furnes or smoke are present.

Stight petroleum odor, blue film top side, release paper back side

Flarenable Limits

LEL

N/A

UNUSUAL FIRE AND EXPLOSION HAZARDS: On burning SO<sub>2</sub> and CO<sub>2</sub>. Main combustion products are H<sub>2</sub>O, CO<sub>2</sub> and C (as heavy smoke).

(Reproduce Locally)

Appearance and Odor

FLASK POINT (Mothod Used):

OSHA 174, Sept. 1985

UEL

NA

SECTION V RE	ACTIVITY	ATA							
	Unstable	<u> </u>	Conditions t	o avold: N/A					
97ABILITY	Stable	×							
WOODER A THEFE THE	44-24-2	1 1			and the Control				
INCOMPATIBILITY	MATHEMATIC TO A	<i>чому:</i> Е	KOBBSIVE NEBL	approaching th	ash point, st	rong oxidizing	agents as	nd acids.	
HAZARDOUS DEC	OMPOSITION C	OR BYPR	ODUCTS: N/A	ı					
HAZARDOUS POLYMERIZATION	May Occur		Conditions to	Avoid N/A					
	Will not Occur	×							
SECTION VI H									
ROUTE(S) OF ENTI			Eye	s7 YES	Sk	in? YES		Ingestion?	YES
HEALTH HAZARDS	(Acute and Cl	ronic):							
IF INHALED:	f burning inhala	nou at the	ues canses us	Uses, headach	he and dizzir	iess. Fumes	may be in	tant to respi	atory tract.
IF INGESTED:	N/A								
IF ON SKIN:	N/A								
	Fumes may be								
EMERGENCY AND	FIRST AID PR	DCEDUR	E8:			_			
IF IN EYES:	Flush with runni	ing water	for at least 15	minutes, seek	medical atte	ntion.			
IF ON SKIN;	For cold produc	wash sk	in with soap ar	nd water.					
IF INGESTED:	ingestion is unifi quantities are in	kely but if gested ho	k happens DO wever get me	NOT INDUCI dical advise.	E VOMITING	i. In general i	no treatme	nt is necess	ary unless large
IF INHALED:	Remove victim	lo fresh al	r, if irritation pe	rsists adminis	ter oxygen s	nd get medic	al attentio	7.	
SECTION VII	RECAUTIO	NS FO	R SAFE HA	NDLING A	ND USE				
STEPS TO BE TAKE	EN IN CASE M	ATERIAL	IS RELEASE	O OR SPILLE	D: If produ	ct has been h	eated and	released for	on solid form allow to
cool and solidify. Bri									
WASTE DISPOSAL	METHOD: Bu	ry in appr	oved landfill or	burn in an (mp	proved incine	erator as per k	ocal regula	tions.	
PRECAUTIONS TO	BE TAKEN IN	HANDL II	IG AND STOR	PAIG: Store in	a dry cool s	res omterter	f from the		
				and Conc an	d ary, 000, 0	nea proteotor	a nom unc	<u> </u>	
								···	
OTHER PRECAUTA	ONS: NA								
OTHER PRECAUTE	ma: rur								
SECTION VIII	ONTROL N	EASI IS	DES						
RESPIRATORY PR									
7.20.7.20.7.7.7.7.7.7.7.7.7.7.7.7.7.7.7.	LOC	AL EXH	UST:	N/A					
VENTILATION	SPE	CIAL:		N/A					
	ME	CHANICA	L (General):	N/A					
	077	ER:		N/A					
DOOTECTIVE OF O	ÆÉ: Barrer	ndod							
PROTECTIVE GLOV EYE PROTECTION:		KREO							
OTHER PROTECTS		OR FOI	DAMEN'T: I	cleaved doll-	Ind Recommen	nded			
WORK LYCHEUD I	BACTICE. NO			PAGE ACT CHORUS	- IN LEGISION	······································			

PAGE 2 (Sheet #936 )